

AVOCOR S SERIES DATASHEET

65" | 75" | 86"



OVERVIEW

The Avocor S Series is a part of our portfolio designed to elevate educational environments, combining sleek design with advanced touch technology. Ideal for classrooms, lecture halls, and hybrid learning settings, the S Series ensures every interaction is engaging and intuitive.

Ensure every educational session, whether in-person or remote, is seamless with the Avocor S Series. Its modern aesthetics and robust functionality make it the perfect solution for schools and universities seeking high performance, interactive displays.

Its diverse connectivity options support seamless integration with various educational tools and devices.

Preloaded with applications like Bytello Class, Note, Share, and Browse*, the S Series transforms standard lessons into interactive experiences, keeping students engaged and informed. For environments requiring Google's ecosystem, the S Series can also be configured with the Avocor Google EDLA certified slot-in OPS Android PC, offering seamless integration with Google Classroom and other Google productivity tools, making it a versatile solution for modern educational challenges.

SOLUTION

Highlights



3 Sizes to choose from

Available in 65", 75", and 86" sizes to fit various classroom and lecture hall needs.



A clear view for all students

The 4K Ultra HD resolution (3840 x 2160 @ 60Hz) provides crystal-clear visuals, enhancing the learning experience by displaying detailed content with stunning accuracy.



Easy applications for teaching & learning

The Avocor S Series supports a wide range of software, including preloaded applications like Bytello Class, Note, Share, and Browse*, ensuring adaptability to diverse educational needs and environments.



Ready for Google EDLA deployments

Upgrade to a certified Google EDLA display using the optional Avocor Slot-in OPS PC to enjoy an immersive Google experience without sacrificing energy efficiency.



SPECIFICATIONS

ize Backlight Aspect Ratio Besolution Besponse Time	65"	75"	86"
Aspect Ratio		D:+ I:+ I ED	
Resolution	Direct-lit LED		
	16:9		
Response Time	3840 x 2160 @ 60Hz		
<u>'</u>	6.5 ms		
Brightness	350 (cd/m2) with zero-bonded glass		
Contrast Ratio	5000:1		
/iewing Angle	178° / 178°		
supported Colors	10 Bit 1.07 Billion Color		
Operation Time	16 hours x 7 days		
Display Orientation		Landscape	
OUCH SYSTEM			
ouch		Up to 40 points touch + 1 stylus	
CPU CPU			
CPU	A55 x 4		
GPU PU	Mali G52 MP2		
AM/ROM	RAM/ROM 8 GB / 64 GB		
android version	Android 13		
CONNECTIVITY			
ide Inputs	2 x HDMI 4K@60Hz, HDCP 2.1, CEC, ARC (HDMI 1), 1 x HDMI out, VGA, 2 x USB-A 3.0, 1 x USB-B 2.0		
ront Inputs/Guest Inputs	1 x Type C (PD 65W), 1 x HDMI, 1 x USB-B 2.0		
vudio	Audio 1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)		
Control	Control 1 x IR input, 1 x RS-232, 2 x LAN Ethernet (RJ-45)		
DPS Slot	Yes, 3840 x 2160 @60Hz		
ViFi	WiFi 6		
AUDIO			
Built-in Speakers	2 x 16W - spatial-stereo front facing		
Aicrophone Array	N/A		
Camera	N/A		
DISPLAY & REMOTE FUNCTIONS			
auto-Source-Detection	Yes		
nage Settings	Yes		
PHYSICAL SPECIFICATIONS			
creen Dimensions (L x W x H)	1488.4 x 896.6 x 87.2 mm / 58.60 x 35.30 x 3.43 inches	1709 x 1020 x 88 mm / 67.28 x 40.16 x 3.46 inches	1957 x 1160 x 100 mm / 77.05 x 45.67 x 3.94 inches
	30.00 x 33.30 x 3.43 inches	07.20 X 40.10 X 3.40 IIICHES	77.03 X 43.07 X 3.74 III.d les
Bezel Dimensions	1628 x 1005 x 208 mm 64.09 x 39.57 x 8.19 inches	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inches	2110 x 1283 x 225 mm 83.07 x 50.51 x 8.86 inches
Shipping Dimensions (L x W x H)	1350 x 152 x 837mm /	1600 x 178 x 960mm /	1840 x 230 x 1103mm /
	53.1 x 5.9 x 32.9 inches	62.9 x 7.0 x 37.7 inches	72.4 x 9.0 x 43.4 inches
Veight (Net)	34.3 kgs / 75.62 lbs	47.30 kg / 104.28 lbs	58.5 kgs / 128.97 lbs
Veight (Gross)	44.75 kgs / 98.66 lbs	60.75 kgs / 133.93 lbs	72.7 kgs / 160.28 lbs
Vall Mount (VESA)	600 x 400	800 x 400	800 x 400
PC Mount		None	
Handles	2		
POWER			
i	<360W	<360W	<520W
Max Power Consumption	\30UVV		\32000
Power Supply	AC100-240V (worldwide), 50/60Hz		
itandby		≤0.5W	
NVIRONMENTAL			
Operating Temperature	0-40°C, 10-90% RH non-condensing		
torage Temperature	-20-60°C, 10-90% RH non-condensing		
Humidity	See above		
VHAT COMES IN THE BOX			
	1 x Remote control, 2 x 3mm fine-tip pass	ive touch styluses, AC power cord,1 x USB-B 3.0 c	able, 1 x HDMI cable, 1 x Quick Start Guide
VARRANTY	tp pass	, , ,,	, \ \ and



Upgrade your solution with:

www.avocor.com



5 Year Warranty



Avocor EDLA OPS PC









